

MoCA Point of Entry Filter

Cable Innovations MoCA[®] Filter (CI-MoCA) offers superior durability and precision specifications in a compact size. The MoCA filter, deployed between the multi-tap and the point of entry, prevents interference from outside sources when installing multi-room DVR systems.

MoCA Filters are also available on all DIU Series products.

PRODUCT FEATURES

- Pass band 5-1000 MHz, stop band 1125-3000 MHz
- Length 41.5 mm, weight 13.7 grams
- One piece design for reduced radiation
- Solid mechanical construction
- 7/16 hex head for convenience of installation
- Waterproof at both ends to IEC529 IP67 standards (15psi)
- Salt spray performance is compliant with SCTE IPS-TP-406—all criteria
- 6KV Surge protection
- 360 degree center conductor provides high tooling & twisting force (>50kg)
- Exceeds SCTE recommendations for standard F-port mating male center conductors (0.56mm to 1.30mm diameter)
- F port conforms to ANSI/SCTE 01 2006
- RFI > 100 dB
- Two (2) Year Warranty

NEW !!



Model No.	CI-MoCA	Test(-dB)
Item	FREQ (MHz)	QA
Insertion Loss (IN-OUT)	5 ~ 1002	1.5
	1125 ~ 1179	35
	1180 ~ 2600	50
Return Loss (ALL)	2601 ~ 3000	40
	5 ~ 65	20
	66 ~ 1002	15
	1125 ~ 1300	1.0
Group Delay	1301 ~ 1550	1.0
	1551 ~ 3000	2.5
Group Delay	5 ~ 1002	5nsec

